CLAIMS

What is claimed is:

1. A method comprising:

accessing a data block, the data block one of a plurality of data blocks mapped to

a physical sector, each data block containing a user data segment and an associated IMD

segment, each IMD segment including a version identifier IMD and at least one other

type of IMD; and

validating the data block by verifying the version identifier IMD and at least one

of the at least one other type of IMD.

2. The method of claim 1, wherein the at least one other type of IMD comprises

checksum IMD.

3. The method of claim 1, wherein the at least one other type of IMD comprises

logical block address IMD.

4. The method of claim 1, wherein the at least one other type of IMD comprises

checksum IMD and logical block address IMD.

5. The method of claim 1 wherein verifying the version identifier IMD includes

determining that a first version identifier stored within the data block matches a second

version identifier stored outside of the data block.

6. The method of claim 2 wherein verifying the checksum IMD includes

determining that a checksum stored within the data block matches a checksum obtained

Patent Application 073103/(TAV:elc)

Page 25 of 30

082225.P7136X

Express Mail No.: EV 305340874 US

by applying a process to a user data contained within the user data segment of the data block, the process being a same process used to create the checksum IMD.

7. The method of claim 3 wherein verifying the logical block address IMD includes determining that a logical block address stored within the data block matches a logical block address used to access the data block.

8. The method of claim 1 wherein the at least one other type of IMD to be verified is selected based upon an expected type of data corruption.

9. The method of claim 8 wherein the at least one other type of IMD to be verified is LBA IMD and the expected type of data corruption is a misdirected memory access operation.

10. The method of claim 8 wherein the at least one other type of IMD to be verified is checksum IMD and the expected type of data corruption is an erroneous WRITE operation.

11. A machine-readable medium containing instructions which, when executed by a processing system, cause the processing system to perform a method, the method comprising:

accessing a data block, the data block one of a plurality of data blocks mapped to a physical sector, each data block containing a user data segment and an associated IMD segment, each IMD segment including a version identifier IMD and at least one other type of IMD; and

Patent Application 073103/(TAV:elc)

Page 26 of 30 08.

082225.P7136X Express Mail No.: EV 305340874 US validating the data block by verifying the version identifier IMD and at least one

of the at least one other type of IMD.

12. The machine-readable medium of claim 11, wherein the at least one other type of

IMD comprises checksum IMD.

13. The machine-readable medium of claim 11, wherein the at least one other type of

IMD comprises logical block address IMD.

14. The machine-readable medium of claim 11, wherein the at least one other type of

IMD comprises checksum IMD and logical block address IMD.

15. The machine-readable medium of claim 11 wherein verifying the version

identifier IMD includes determining that a first version identifier stored within the data

block matches a second version identifier stored outside of the data block.

16. The machine-readable medium of claim 12 wherein verifying the checksum IMD

includes determining that a checksum stored within the data block matches a checksum

obtained by applying a process to a user data contained within the user data segment of

the data block, the process being a same process used to create the checksum IMD.

17. The machine-readable medium of claim 13 wherein verifying the logical block

address IMD includes determining that a logical block address stored within the data

block matches a logical block address used to access the data block.

18. The machine-readable medium of claim 11 wherein the at least one other type of

IMD to be verified is selected based upon an expected type of data corruption.

Patent Application 073103/(TAV:elc)

Page 27 of 30

082225.P7136X

Express Mail No.: EV 305340874 US

- 19. The machine-readable medium of claim 18 wherein the at least one other type of IMD to be verified is LBA IMD and the expected type of data corruption is a misdirected memory access operation.
- 20. The machine-readable medium of claim 18 wherein the at least one other type of IMD to be verified is checksum IMD and the expected type of data corruption is an erroneous WRITE operation.
- 21. A data storage system comprising:
 - a storage media;
 - a processing system; and
- a memory, coupled to the processing system, characterized in that the memory has stored therein instructions which, when executed by the processing system, cause the processing system to a) access a data block, the data block one of a plurality of data blocks mapped to a physical sector, each data block containing a user data segment and an associated IMD segment, each IMD segment including a version identifier IMD and at least one other type of IMD, and b) validate the data block by verifying the version identifier IMD and at least one of the at least one other type of IMD.
- 22. The data storage system of claim 21, wherein the at least one other type of IMD comprises checksum IMD.
- 23. The data storage system of claim 21, wherein the at least one other type of IMD comprises logical block address IMD.

Patent Application 073103/(TAV:elc)

Page 28 of 30

082225.P7136X Express Mail No.: EV 305340874 US 24. The data storage system of claim 21, wherein the at least one other type of IMD

comprises checksum IMD and logical block address IMD.

25. The data storage system of claim 21 wherein verifying the version identifier IMD

includes determining that a first version identifier stored within the data block matches a

second version identifier stored outside of the data block.

26. The data storage system of claim 22 wherein verifying the checksum IMD

includes determining that a checksum stored within the data block matches a checksum

obtained by applying a process to a user data contained within the user data segment of

the data block, the process being a same process used to create the checksum IMD.

27. The data storage system of claim 23 wherein verifying the logical block address

IMD includes determining that a logical block address stored within the data block

matches a logical block address used to access the data block.

28. The data storage system of claim 21 wherein the at least one other type of IMD to

be verified is selected based upon an expected type of data corruption.

29. The data storage system of claim 28 wherein the at least one other type of IMD to

be verified is LBA IMD and the expected type of data corruption is a misdirected

memory access operation.

30. The data storage system of claim 28 wherein the at least one other type of IMD to

be verified is checksum IMD and the expected type of data corruption is an erroneous

WRITE operation.

Patent Application 073103/(TAV:elc)

Page 29 of 30

082225.P7136X

Express Mail No.: EV 305340874 US